

## Declaration of Performance

No.: SAFE-561-54(T)

1.	Unique identification code of the product-type:	<b>SAFE-561-54(T)</b>
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	<b>See product label and marking</b>
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	<b>Loudspeaker to be used for personal address, voice alarm and background music.</b>
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	<b>DNH AS Gruveveien 2-4 3770 Kragerø Norway</b>
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	<b>Not relevant</b>
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	<b>System 1</b>
7.	In case of the declaration of performance concerning a construction product covered by a harmonized standard:	<b>EN 54-24:2008 Notified testing laboratory Centrum Naukowo-Badawcze Ochrony Przeciwpożarowej.</b>
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	<b>Not relevant</b>

## 9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Sensitivity 100Hz-10KHz 1/3 Oct. Pink noise total 1W/4 Meters	100Hz: 35dB 125Hz: 43dB 160Hz: 51dB 200Hz: 58dB 250Hz: 62dB 315Hz: 67dB 400Hz: 65dB 500Hz: 64dB 630Hz: 64dB 800Hz: 64dB 1KHz: 62dB 1250Hz: 65dB 1600Hz:67dB 2KHz: 67dB 2500Hz: 67dB 3150Hz:71dB 4KHz: 72dB 5KHz: 69dB 6300Hz:69 dB 8KHz: 68dB 10KHz: 59dB	EN 54-24:2008
Weight	1,2kg	
Max/min amb temp	90 °C / -20°C	
IP rating	IP22	
Rated /max power	6W / 6W	
Tappings	0,5W 1,5W 3W 6W	
Voltage	70V or 100V Line	
Horizontal coverage angles (HCA) / Vertical coverage angles (VCA) (÷6dB)	1 Oct. Pink noise 500Hz 360° 1 Oct. Pink noise 1K Hz 160° 1 Oct. Pink noise 2K Hz 105° 1 Oct. Pink noise 4K Hz 85°	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Kenneth Williams - Quality Assurance Manager

Kragerø, Norway 14.10.2013

