




G715-Pro Features

- 3-way compact versatile full range system
- Unique 1.4" mid/high coaxial neodymium driver
- 15" neodymium ultra low distortion woofer
- Passive or bi-amplified operation
- Designed for fixed installation, touring and stage monitoring



3-way high output versatile full range system, Unique 1.4" mid/high coaxial neodymium driver

The CODA G715-Pro is a versatile full range three-way loudspeaker system that features a high power 15" neodymium woofer and a 1.4" mid/high coaxial neodymium driver coupled to a 90° x 60° rotatable elliptical waveguide.

As a 3-way system the G715-Pro may be driven passively or with bi-amplification to provide extremely high output. The CODA G715-Pro is a powerful solution for front of house touring, installed PA for theatres, clubs and corporate events or as a stage monitor.



Data Sheet G715-Pro





3-way high power full range system, multidesign enclosure Product type: Dimensions (WxHxD): 420 x 700 x 370 mm / 16.54 x 27.56 x 14.57" Dimensions including hardware N/A (WxHxD): 24.5 kg / 54.01 lbs Net weight: Frequency response: 50 Hz – 23 kHz (-6 dB) Power handling AES / peak (passive): 1000 W / 4000 W 1000 W / 4000 W - Low AES / peak: - Mid / High AES / peak: 150 W / 1300 W Max. peak SPL (with LINUS10):* 143 dB Dispersion horizontal: 90° Dispersion vertical: 60° 15" neodymium woofer, 4" (101.6 mm) voice coil, 1000 W Components Low frequency: (AES) 1.4" neodymium coaxial driver, 3.5" (90 mm) + 1.75" (44.4 Components Mid/High frequency: mm) voice coil, 150 W + 80 W (AES) 750 Hz, 6.3 kHz passive Crossover point: 2 x Neutrik™ NL4MP Input connectors: Nominal impedance LF / MF+HF: 8Ω(+1/-1) Enclosure material: Birch plywood

G715-Pro Data Sheet

Suspension:


*Measured with pink noise 6 dB crest factor. Half-space loading.





35° 55° -°

M6 and M8 threaded points for use with optional U-bracket



Other G-Series Related Products



G15-SUB Compact, High-Output Subwoofer CODA AUDIO GmbH



G18-SUB Extended Low Frequency Subwoofer



LINUS10-C 4-Channel Loudspeaker Management Amplifier



Boulevard der EU 6, 30539 Hannover, Expo Park, Germany E-Mail: contact@codaaudio.com Website: www.codaaudio.com